

*What do you get when you cross a **Hot Dawg** unit heater with a **Hydronic** unit heater?*

You get the new **Hot Dawg H₂O[®]**!!!



- **Two Model Sizes:** HHD 30 and HHD 45.
- **Low Profile Design:** Ideally suited for residential garages, basements, vestibules, commercial, industrial, institutional installations (non-potable water applications only).
- **Attractive:** Hammertone Beige paint color.
- **Flexible Mounting Orientations:** Two L-shaped mounting brackets for:
 - Horizontal air delivery, mounted parallel to 16" O.C. joists
 - Horizontal air delivery, mounted perpendicular to 16" O.C. joists
 - Vertical air delivery, mounted between 16" O.C. joists
- **Side Access:** Electrical connections are standard on the left with piping on the right (easily reversed in the field by simply flipping the unit over).
- **High Capacity Coil:** 2-row hot water coil (up to 200°F), with 1/2" NPT piping connections.
 - Allows for higher leaving air temperature
 - Output higher when compared to HSB units
 - Good low water temperature performance
- **Twin Blower Wheels:** Designed for quieter operation.
 - Quieter operation
 - Enclosed blower wheels for safer operation of fan
- **Motor:** Single dual shaft motor, 115V/60Hz/1ph operation. HHD 45 comes standard with a factory installed solid state speed controller.
- **Vibration Isolation:** Factory supplied neoprene vibration isolators.



300 Pond St. Randolph, MA 02368 | Phone: (800) 346 - 9215 Fax: (781) 986 - 2028