

## Model Selection

Model	Description H x W x D (in)	Airflow cfm (L/s)					Effectiveness @ 0 °C (32 °F)	Performance Highlights
		.1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)		
<b>95 MAX</b>	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Compact design for tight installations. Three top ports and 4th port knockout allows top or side mounting.
<b>155 MAX</b> <b>155 MAX RX</b>	Recirculating Defrost 19 x 33.62 x 14.75	150 (71)	146 (69)	134 (63)	121 (57)	106 (50)	76%	Most popular HRV. Horizontal w/ door port balance. Same as 155 MAX, reverse design.
<b>155 ECM</b>	Recirculating Defrost 19 x 33.62 x 14.75	164 (77)	157 (74)	147 (69)	146 (69)	140 (66)	72%	Same design as 155 MAX, with a highly efficient energy-saving ECM motor.
<b>200 MAX</b> <b>200 MAX RX</b>	Recirculating Defrost 19 x 33.62 x 14.75	207 (97)	200 (94)	184 (87)	171 (80)	152 (71)	74%	Versatile performance in a variety of regions. Same as 200 MAX, reverse design.
<b>MAXTOP</b>	Recirculating Defrost 25.5 x 22.5 x 26.5	196 (93)	188 (89)	178 (84)	165 (78)	149 (70)	80%	Ports at 45° for easy top or horizontal mounting. Makes installation possible in tighter spaces.
<b>195 DCS</b>	Damper Defrost 19 x 49 x 14.75	203 (96)	191 (90)	182 (86)	167 (79)	155 (73)	88%	Dual core for max heat recovery & energy efficiency. Also available with an ECM motor.
<b>300 DCS</b>	Damper Defrost 19 x 49 x 14.75	265 (125)	260 (123)	250 (118)	235 (111)	220 (104)	90%	Same design as 195 DCS except for greater airflows. Meets the needs of high-efficiency in larger homes.
<b>200 ERV</b> <b>200 ERVD</b>	No Defrost Damper Defrost 19 x 33.62 x 14.75 (both)	180 (85)	169 (79)	157 (74)	146 (68)	132 (62)	76%	For warm, humid regions with temperatures above -4 °C Same design as 200 ERV with damper and 5 ports.



Setting a new standard  
for energy efficient, clean air homes



Visit us at [www.lifebreath.com](http://www.lifebreath.com)

Manufacturer reserves the right to change specifications without notice.

## Control Options



Lifestyle MAX  
Digital Control  
#99-DXPL01  
(included)



or choose...  
Lifestyle MAX  
Programmable  
Control  
#99-LS01

- 5-speed operation
- 4 user operational modes
  - continuous ventilation
  - 20 min. ON, 40 min. OFF
  - 20 min. ON, 40 min. recirculation\*
  - continuous recirculation\*
- \* Not available on all models
- Built-in interface to furnace
- Automatic service reminder
- **DELUXE** fully featured 5-speed, 4 mode unit.
- Fully **PROGRAMMABLE**, allowing you to customize for your specific lifestyle.
- Automatic control based on outdoor temperature sensing.

## Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiate high speed operation for 20, 40 or 60 min.

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 min.



## Model Selection

Model	Description H x W x D (inches)	Airflow cfm (L/s)					Effectiveness @ 0 °C (32 °F)	Performance Highlights
		.1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)		
RNC 95	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Top ported, compact unit. Ideally suited to narrow installations.
RNC5-TPD	Recirculating Defrost 18.75 x 27 x 15	169 (80)	156 (73)	149 (70)	136 (64)	126 (59)	74%	Top ported unit. Ideally suited to narrow installations.
RNC 120D	Recirculating Defrost 22 x 22.13 x 9.13	142 (67)	137 (64)	131 (62)	128 (60)	123 (58)	68%	Only 9 inches tall. Can be mounted horizontally or vertically for maximum installation flexibility.
RNC 155	Recirculating Defrost 19 x 33.62 x 14.75	150 (71)	146 (69)	134 (63)	121 (57)	106 (50)	76%	Horizontal model, with door port balancing. One of our most popular units.
RNC 200	Recirculating Defrost 19 x 33.62 x 14.75	207 (97)	200 (94)	184 (87)	171 (80)	152 (71)	74%	Horizontal model, with door port balancing. Same design as RNC 155 with greater airflow.
RNC 10	Damper Defrost 19 x 33.62 x 14.75	177 (83)	164 (77)	156 (73)	143 (67)	123 (58)	76%	Horizontal model with 5 ports and damper defrost. Best value for new construction.
RNC 20	Damper Defrost 19 x 33.62 x 14.75	214 (101)	206 (97)	193 (91)	184 (87)	170 (80)	67%	Same design as RNC 10. Ideally suited to larger applications.



Setting a new standard  
for energy efficient, clean air homes



Visit us at [www.lifebreath.com](http://www.lifebreath.com)

Manufacturer reserves the right to change specifications without notice.

## Control Options



Lifestyle  
Dehumidistat  
#99-DH01

- Initiates high speed ventilation when the indoor humidity level is above the set point.



Lifestyle RNC  
Ventilation  
Control  
#99-BC01

- 2 Speed operation
- Standby
- Unit On/Off
- Dehumidistat



Lifestyle RNC Digital Control #99-DX01

- 4 selectable operational modes\*  
\*Not available on all models
- 2 speed operation on each mode
- Adjustable dehumidistat function
- Dehumidistat disable

## Timers

### Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 min.

### Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 min.

## Accessories

- Weather Hoods - 5", 6" or 7"
- Kitchen Grille - 6" x 10"
- Tech Grilles - 4", 5", 6" or 8"